



INVINCIBLE BEAM CAPACITIES

ANSI MH 16.1 2012

(3-PIN CONNECTORS)

LENGTH	IBX30	IBX35	IBX39	IBX43	IBX48	IBN48	IBN55	IBN60	IBH60
48	7,580	9,080	10,470	11,840	13,970	16,210	19,480	22,200	27,470
60	6,300	7,480	8,590	9,670	11,360	13,150	15,750	17,910	22,140
72	5,240	6,420	7,320	8,220	9,610	11,110	13,260	15,050	18,580
84	4,010	5,310	6,420	7,170	8,370	9,650	11,480	13,010	16,040
90	3,560	4,700	5,850	6,760	7,860	9,070	10,770	12,190	15,020
92	3,430	4,520	5,620	6,630	7,710	8,890	10,560	11,940	14,710
94	3,310	4,350	5,400	6,510	7,560	8,720	10,350	11,700	14,410
96	3,190	4,190	5,210	6,270	7,430	8,560	10,150	11,480	14,130
98	3,080	4,040	5,020	6,040	7,290	8,390	9,960	11,260	13,850
100	2,970	3,910	4,840	5,830	7,160	8,240	9,780	11,040	13,590
102	2,880	3,770	4,670	5,620	7,040	8,100	9,600	10,850	13,340
104	2,780	3,650	4,510	5,430	6,920	7,910	9,430	10,650	13,110
106	2,700	3,520	4,360	5,240	6,730	7,630	9,260	10,460	12,880
108	2,610	3,410	4,220	5,060	6,510	7,380	9,100	10,280	12,650
110	2,530	3,300	4,080	4,900	6,290	7,130	8,960	10,110	12,430
112	2,460	3,200	3,950	4,740	6,080	6,890	8,810	9,950	12,230
114	2,380	3,110	3,830	4,600	5,890	6,670	8,670	9,780	12,020
116	2,320	3,010	3,710	4,450	5,700	6,450	8,530	9,620	11,830
118	2,250	2,930	3,600	4,320	5,520	6,250	8,250	9,470	11,640
120	2,190	2,840	3,500	4,190	5,360	6,060	8,000	9,330	11,460
132	1,870	2,410	2,960	3,530	4,500	5,080	6,690	8,150	9,800
138	1,730	2,230	2,740	3,260	4,150	4,690	6,150	7,490	9,010
144	1,610	2,080	2,540	3,020	3,840	4,330	5,680	6,910	8,300
156	1,410	1,810	2,210	2,630	3,320	3,740	4,890	5,940	7,130
168	1,250	1,600	1,950	2,300	2,910	3,270	4,270	5,170	6,190